

THAT WHICH IS CLAIMED IS:

1. A method (400) of compressing a digital image including a matrix of elements each one consisting of a plurality of digital components of different type representing a pixel, the method

5 comprising the steps of:

splitting (455) the digital image into a plurality of blocks and calculating, for each block, a group of DCT coefficients for the components of each type,

10 quantizing (460-465) the DCT coefficients of each block using a corresponding quantization table scaled by a gain factor for achieving a target compression factor,

characterized by the steps of

15 determining (440) at least one energy measure of the digital image,

estimating (441-450) the gain factor as a function of the at least one energy measure, the function being determined experimentally according to

20 the target compression factor.

2. The method (400) according to claim 1, wherein each group of DCT coefficients consists of a DC coefficient and a plurality of AC coefficients, the step (441-450) of estimating the gain factor including

5 the steps of:

estimating (441) a first number of bits required to encode the AC coefficients of all the blocks using the quantization tables scaled by a pre-set factor as a first function of the at least one

10 energy measure, the first function being determined

09902439 01001

calculating (442) a second number of bits required to encode the DC coefficients of all the blocks using the quantization tables scaled by the pre-set factor,

estimating (450) the gain factor as a second function of the basic compression factor, the second function being determined experimentally according to the target compression factor.

4. The method (400) according to claim 2 or 3, wherein the step of estimating (443-445) the basic compression factor includes the steps of:

5. The method (400) according to any claim from 2 to 4, further comprising the steps of:

storing a plurality of sets of parameters
representing the second function, each set of
5 parameters being associated with a corresponding value
of the target compression factor,

selecting (410) an image quality and
determining a current value of the target compression
factor as a function of the selected image quality,
10 reading (450) the parameters associated with
the current value of the target compression factor and
estimating the gain factor using the read parameters.

6. The method (400) according to any claim
from 2 to 5, wherein the pre-set factor is determined
experimentally according to the target compression
factor.

7. The method (400) according to any claim
from 1 to 6, wherein each element of the digital image
consists of a luminance component, a first chrominance
component, and a second chrominance component.

8. The method (400) according to claim 7,
wherein the at least one energy measure consists of a
total energy measure equal to the sum of an energy
measure of the luminance components, an energy measure
5 of the first chrominance components and an energy
measure of the second chrominance components.

9. The method (400) according to claim 7 or
8, wherein the step (440) of determining the at least
one energy measure comprises, for each type of
component, the steps of:

FOOT 40" 6420660

- 5 calculating a horizontal Sobel image and a
vertical Sobel image by means of a convolution of the
elements of the digital image consisting of said type
of component with a horizontal mask and a vertical
mask, respectively,
- 10 calculating a total Sobel image by summing
the horizontal Sobel image and the vertical Sobel
image, and
 summing the absolute value of each element of
the total Sobel image.

10. The method (400) according to claim 9,
wherein at least one quantization table is asymmetric
along a horizontal direction and a vertical direction,
the method further comprising the steps of:

- 5 multiplying the Sobel image associated with
the at least one quantization table by a correction
factor for compensating the asymmetry of the
corresponding quantization table.

11. The method (400) according to any claim
from 1 to 10, further comprising the steps of:

- providing (410-430) an incomplete digital
image wherein at least one component is missing in each
5 element,

 obtaining (435) the digital image from the
incomplete digital image,

- storing (438) the digital image onto a
working memory and concurrently performing the steps of
10 determining (440) the at least one energy measure and
estimating (441-450) the gain factor,

 reading (455-465) the digital image from the
working memory for performing the steps of splitting

(455) the digital image and quantizing (460-465) the
15 DCT coefficients.

12. The method (400a) according to any claim
from 1 to 10, further comprising the steps of:

providing (410-430) an incomplete digital
image wherein at least one component is missing in each
5 element,

obtaining (435) the digital image from the
incomplete digital image for performing the steps of
determining (440) the at least one energy measure and
estimating (441-450) the gain factor,

10 obtaining (435a) the digital image from the
incomplete digital image again for performing the steps
of splitting (455) the digital image and quantizing
(460-465) the DCT coefficients.

13. A device (115) for compressing a digital
image including a matrix of elements each one
consisting of a plurality of digital components of
different type representing a pixel, the device (115)
5 comprising means (145) for splitting the digital image
into a plurality of blocks and calculating, for each
block, a group of DCT coefficients for the components
of each type, means (150) for quantizing the DCT
coefficients of each block using a corresponding
10 quantization table scaled by a gain factor for
achieving a target compression factor,

characterized in that

the device (115) further includes means (190)
for determining at least one energy measure of the
15 digital image, and means (170) for estimating the gain
factor as a function of the at least one energy

0906139-071001
100120-6E120660

measure, the function being determined experimentally according to the target compression factor.

14. The device (115) according to claim 13, further comprising a compression unit (135) comprising the means (145) for splitting the digital image and calculating the DCT coefficients and the means (150) for quantizing the DCT coefficients, a memory unit (175) for storing the quantization tables, an energy unit (190) including the means for determining the at least one energy measure, a processor unit (170) for controlling the device (115), communication means (120) for connecting the compression unit, the memory unit, the energy unit and the processor unit therebetween, the processor unit (170) estimating the gain factor under the control of a program stored onto the memory unit (175).

15. A digital still camera (100) comprising means (105-130) for providing the digital image and the device (115) of claim 13 or 14.